

2012 Drill Results at Main Longstreet ( $\geq 5$  feet @  $\geq 0.01$  oz/ton gold equivalent)

Hole No.	From (feet)	To (feet)	Interval (feet)	TRUE Width (ft)	Gold (oz/ton)	Silver (oz/ton)	TRUE Width (m)	Gold (g/t)	Silver (g/t)	Au Equiv. (oz/ton)
LS-1202	0	75	75	74.7	0.022	0.342	22.8	0.76	11.7	0.028
including	10	15	5	5	0.154	1.629	1.5	5.26	55.8	0.181
including	85	270	185	184.3	0.018	0.613	56.2	0.61	21	0.028
including	115	180	65	64.8	0.035	0.972	19.7	1.2	33.3	0.051
including	115	140	25	24.9	0.051	1.772	7.6	1.74	60.7	0.08
including	355	430	75	74.7	0.002	0.461	22.8	0.08	15.8	0.01
LS-1203	0	50	50	49.8	0.007	0.388	15.2	0.24	13.29	0.014
including	70	80	10	10	0.004	0.432	3	0.14	14.8	0.011
including	185	335	150	149.4	0.004	0.534	45.6	0.14	18.29	0.013
including	430	445	15	14.9	0.008	0.187	4.6	0.26	6.4	0.011
LS-1204	20	100	80	76.9	0.029	0.532	23.3	1	18.23	0.038
including	45	90	45	43	0.042	0.726	13.1	1.43	24.88	0.054
& including	65	70	5	4.8	0.106	0.95	1.5	3.64	32.55	0.122
including	175	185	10	9.6	0.005	1.548	2.9	0.16	53	0.03
including	195	245	50	47.8	0.006	0.295	14.6	0.21	10.09	0.011
including	315	325	10	9.6	0.002	0.566	2.9	0.08	19.4	0.012
LS-1205	95	105	10	10	0.012	0.24	3	0.4	8.36	0.016
including	110	245	135	135	0.088	0.48	41.1	3.01	16.42	0.096
including	205	215	10	10	0.956	0.64	3	32.73	21.78	0.966
including	205	210	5	5	1.813	1.16	1.5	62.1	39.85	1.833
LS-1206	0	150	150	143.4	0.025	0.69	43.7	0.84	23.8	0.036
including	55	70	15	14.3	0.1	1.24	4.4	3.41	42.47	0.12
& including	105	115	10	9.6	0.044	3.05	2.9	1.5	104.4	0.095
including	180	185	5	4.8	0.005	0.35	1.5	0.17	12.1	0.011
including	205	235	30	28.7	0.013	0.87	8.7	0.45	29.96	0.028
including	360	390	30	28.7	0.004	0.38	8.7	0.14	12.87	0.01
including	395	405	10	9.6	0.004	0.71	2.9	0.13	24.3	0.016
including	425	430	5	4.8	0.005	0.67	1.5	0.17	22.8	0.016
including	455	465	10	9.6	0.001	0.73	2.9	0.04	25.05	0.013
LS-1207	0	130	130	124.3	0.01	0.427	37.9	0.34	14.61	0.017
including	70	75	5	4.8	0.06	1.364	1.5	2.06	46.7	0.083
including	180	185	5	4.8	0.008	0.166	1.5	0.26	5.7	0.01
including	200	235	35	33.5	0.011	0.314	10.2	0.38	10.74	0.016
including	270	285	15	14.3	0.001	0.828	4.4	0.05	28.37	0.015
including	370	375	5	4.8	0.002	0.666	1.5	0.08	22.8	0.013
LS-1208	0	25	25	24.8	0.014	0.415	7.5	0.48	14.2	0.021
including	45	120	75	74.3	0.027	0.485	22.6	0.94	16.59	0.035
including	105	110	5	5	0.271	4.03	1.5	9.29	138	0.338
including	180	190	10	9.9	0.051	0.656	3	1.73	22.48	0.061
LS-1209	0	245	245	244.1	0.008	0.449		0.29	15.39	0.016
including	75	85	10	10	0.042	0.772		1.44	26.43	0.055
including	280	325	45	44.8	0.012	1.701		0.41	58.24	0.04
including	290	295	5	5	0.037	7.942		1.27	272	0.169
LS-1210	210	300	90.0	86.1	0.003	0.63	26.2	0.09	21.71	0.013
including	395	400	5.0	4.8	0.012	0.64	1.5	0.42	22.00	0.023
LS-1211	0	190	190.0	181.7	0.006	0.30	55.4	0.22	10.16	0.011
including	60	65	5.0	4.8	0.057	0.81	1.5	1.94	27.65	0.070
LS-1212	0	10	10.0	9.6	0.014	0.33	2.9	0.47	11.25	0.019
including	45	55	10.0	9.6	0.005	0.44	2.9	0.16	15.20	0.012
including	140	355	215.0	205.6	0.003	0.56	62.7	0.11	19.12	0.013
LS-1213	0	45	45.0	43.0	0.008	0.12	13.1	0.26	4.04	0.010
including	70	220	150.0	143.4	0.020	0.39	43.7	0.68	13.41	0.026
LS-1214	0	165	165.0	157.8	0.011	0.33	48.1	0.386	11.195	0.017
including	120	130	10.0	9.6	0.049	0.60	2.9	1.69	20.65	0.059
including	200	205	5.0	4.8	0.002	0.52	1.5	0.07	17.70	0.011
LS-1215	0	200	200.0	191.3	0.024	0.34	58.3	0.82	11.74	0.030
including	160	165	5.0	4.8	0.133	1.24	1.5	4.55	42.55	0.153
including	220	225	5.0	4.8	0.015	0.04	1.5	0.50	1.20	0.015
LS-1216C	5	235	230.0	219.9	0.010	0.49	67.0	0.34	16.71	0.018
including	155	160	5.0	4.8	0.075	0.30	1.5	2.58	10.35	0.080
LS-1217C	0	15	15.0	14.3	0.011	0.29	4.4	0.38	9.83	0.016
including	30	205	175.0	167.4	0.018	0.45	51.0	0.63	15.44	0.026
including	65	75	10.0	9.6	0.103	0.65	2.9	3.52	22.38	0.114
including	230	235	5.0	4.8	0.005	0.69	1.5	0.17	23.80	0.016
LS-1221	0	50	50.0	47.8	0.008	0.23	14.6	0.29	7.92	0.012
including	265	270	5.0	4.8	0.007	0.58	1.5	0.24	19.90	0.017
LS-1222C	5	35	30.0	28.7	0.008	0.32	8.7	0.28	10.85	0.013
including	60	65	5.0	4.8	0.012	0.00	1.5	0.41	0.00	0.012
including	125	220	95.0	90.8	0.017	0.30	27.7	0.58	10.37	0.022
including	180	195	15.0	14.3	0.040	0.93	4.4	1.38	31.93	0.056
LS-1224C	105	120	15.0	14.3	0.021	0.48	4.4	0.74	16.43	0.029
including	150	160	10.0	9.6	0.007	0.19	2.9	0.24	6.55	0.010
including	195	260	65.0	62.2	0.029	2.30	18.9	0.99	78.77	0.067
including	195	205	10.0	9.6	0.176	11.99	2.9	6.02	410.50	0.375
including	200	205	5.0	4.8	0.288	20.00	1.5	9.87	685.00	0.622
including	290	295	5.0	4.8	0.011	0.79	1.5	0.38	26.90	0.024
LS-1223	0	10	10	9.6	0.008	0.26	2.9	0.28	8.75	0.012
including	50	60	10	9.6	0.004	0.7	2.9	0.13	24.1	0.016
including	150	205	55	52.6	0.008	0.56	16	0.26	19.15	0.017
including	240	250	10	9.6	0.003	1.09	2.9	0.1	37.35	0.021
including	375	380	5	4.8	0.015	1.68	1.5	0.51	57.6	0.043
including	395	410	15	14.3	0.005	0.64	4.4	0.18	22.03	0.016
including	490	495	5	4.8	0.002	0.83	1.5	0.08	28.5	0.016
including	505	510	5	4.8	0.002	0.75	1.5	0.07	25.6	0.015
LS-1225	0	20	20	19.1	0.02	0.52	5.8	0.68	17.76	0.028
including	0	10	10	9.6	0.031	0.87	2.9	1.05	29.8	0.045
including	100	105	5	4.8	0.007	0.25	1.5	0.24	8.7	0.011
including	125	320	195	186.5	0.008	0.96	58.8	0.28	33.02	0.024
including	155	160	5	4.8	0.098	6.1	1.5	3.36	209	0.2
& including	310	315	5	4.8	0.043	1.74	1.5	1.46	59.6	0.072
LS-1226	0	105	105	100.4	0.007	0.47	30.6	0.24	15.97	0.015
including	310	405	95	90.8	0.003	0.96	27.7	0.11	32.86	0.019
LS-1227	230	255	25	23.9	0.018	1.07	7.3	0.63	36.76	0.036
including	245	255	10	9.6	0.03	2.1	2.9	1.04	71.95	0.065
including	335	340	5	4.8	0.005	0.58	1.5	0.18	19.9	0.015
including	345	350	5	4.8	0.007	0.6	1.5	0.24	20.6	0.017
including	400	410	10	9.6	0.004	0.93	2.9	0.14	32	0.02
including	420	425	5	4.8	0.005	0.33	1.5	0.18	11.4	0.011
including	495	500	5	4.8	0.002	0.55	1.5	0.08	18.8	0.012